



Hyper-ion™

Heterojunction Hyper-ion Series Bifacial Module

RSM132-8-680-705BHDG

Hyper-link Interconnection

Patented Technology

680-705 W_p

Power Output Range

22.7 %

Higher Efficiency

0~+3%

Positive Power Tolerance



No B-O caused LID



Ultra-high bifacial factor



Ultra-high power generation, ultra-low carbon emission



Most stable power temperature coefficient



Lead technology of metallization process



Excellent anti-LID & anti-PID performance




* As there are different certification requirements in different markets, please contact your local Risen Energy sales representative for the specific certificates applicable to the products in the region in which the products are to be used.

LINEAR PERFORMANCE WARRANTY


15 years product warranty / 30 years linear power warranty

0.3% Annual Degradation over 30 years




* Please check the valid version of Limited Product Warranty which is officially released by Risen Energy Co., Ltd

Dimensions of PV Module




RSM132-8-690BHDG

I-V characteristics at different irradiances



I-V characteristics at different temperatures

(AM1.5, 1000W/m²)



PACKAGING CONFIGURATION

	40ft(HQ)
Number of modules per container	558
Number of modules per pallet	31
Number of pallets per container	18
Packaging box dimensions (LxWxH) in mm	1320×1120×2520
Box gross weight[kg]	1315

ELECTRICAL DATA (STC)

Model Type	RSM132-8-680-705BHDG					
Rated Power in Watts-Pmax(Wp)	680	685	690	695	700	705
Open Circuit Voltage-Voc(V)	49.47	49.56	49.65	49.74	49.83	49.92
Short Circuit Current-Isc(A)	17.48	17.56	17.66	17.74	17.82	17.91
Maximum Power Voltage-Vmpp(V)	41.48	41.56	41.63	41.71	41.78	41.86
Maximum Power Current-Impp(A)	16.41	16.50	16.60	16.68	16.77	16.86
Module Efficiency (%) ★	21.9	22.1	22.2	22.4	22.5	22.7

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.
Bifacial factor: 85±10(%) ★ Module Efficiency (%): Rounding to the nearest number

Electrical characteristics with 10% rear side power gain

Total Equivalent power -Pmax (Wp)	748	754	759	765	770	776
Open Circuit Voltage-Voc(V)	49.47	49.56	49.65	49.74	49.83	49.92
Short Circuit Current-Isc(A)	19.23	19.32	19.43	19.51	19.60	19.70
Maximum Power Voltage-Vmpp(V)	41.48	41.56	41.63	41.71	41.78	41.86
Maximum Power Current-Impp(A)	18.05	18.15	18.26	18.35	18.44	18.55

Rear side power gain: The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.

ELECTRICAL DATA (NMOT)

Model Type	RSM132-8-680-705BHDG					
Maximum Power-Pmax (Wp)	519.3	523.0	527.2	530.9	534.5	538.0
Open Circuit Voltage-Voc (V)	46.35	46.44	46.52	46.61	46.69	46.78
Short Circuit Current-Isc (A)	14.34	14.40	14.48	14.55	14.61	14.68
Maximum Power Voltage-Vmpp (V)	38.78	38.85	38.93	39.00	39.07	39.14
Maximum Power Current-Impp (A)	13.39	13.46	13.54	13.61	13.68	13.76

NMOT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar cells	n-type HJT
Cell configuration	132 cells (6×11+6×11)
Module dimensions	2384×1303×35mm
Weight	41kg
Superstrate	High Transmission, AR Coated Heat Strengthened Glass
Substrate	Heat Strengthened Glass
Frame	High strength alloy steel
J-Box	Potted, IP68, 1500VDC, 3 Schottky by pass diodes
Cables	4.0mm², Positive(+)350mm, Negative(-)230mm (Connector Included)
Connector	Risen Twinset PV-SY02, IP68

TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	43°C±2°C
Temperature Coefficient of Voc	-0.22%/°C
Temperature Coefficient of Isc	0.047%/°C
Temperature Coefficient of Pmax	-0.24%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	35A
Limiting Reverse Current	35A



RISEN ENERGY CO., LTD.

Tashan Industry Zone, Meilin, Ninghai 315609, Ningbo | PRC

Tel: +86-574-59953239

Fax: +86-574-59953599

E-mail: marketing@risenenergy.com

Website: www.risenenergy.com

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

© 2023 Risen Energy. All rights reserved. Contents included in this datasheet are subject to change without notice.

No special undertaking or warranty for the suitability of special purpose or being installed in extraordinary surroundings is granted unless as otherwise specifically committed by manufacturer in contract document.